



Revion Automatic Transmission Fluid

PRODUCT DESCRIPTION:

ATF DEX II is an automatic transmission oil blended with highly refined base stocks and one of the latest additives technologies. It is used in passenger cars and light commercial vehicles. It helps reduce transmission "chatter" assuring a smooth and quiet operation at all speeds under any working condition. Drive II provides optimal oxidation and thermal stability, friction control, cleanliness, load-carrying ability, wear and corrosion protection to ensure the longest life of your transmission.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, power steering, vans, truck and buses where the manufacturer recommends an ATF GM Dexron II D.

FEATURES & BENEFITS:

- Very high viscosity index linked with an excellent viscosity stability in operation
- Very low pour point
- Very good thermal stability
- Excellent resistance to oxidation
- Friction properties specific to the requirements.

PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON IID
- CHRYSLER +3
- VOITH H55.6335
- VOLVO 97355
- FORD ESP-M2C138-CJ / ESP-M2C166-H
- ALLISON TES 389, ALLISON TES 228(C4)
- MB 236.1/236.5/236.7
- ZF TE-ML-04D / 09 / 11A / 14A
- BMW 81 22 9 400 272/81 22 9 400 275/81 22 9 407 738
- CAT TO-2
- TOYOTA TII/2
- MAN 339 TYPE L2/V1
- OPEL 19 40 700 / 19 40 707
- MITSUBISHI SP / SP2/ BTR

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ATF DEX II
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C, min	ASTM D7042	cSvt	7.1
Viscosity Index	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.revionoil.com

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet www.revionoil.com

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 600C, exposed to hot sun or freezing conditions.

™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.