



## Revion Automatic Transmission Fluid

**PRODUCT DESCRIPTION:** ATF DEX III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, loadCarrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.

**APPLICATION:** Suitable for automatic gearboxes of passenger cars, heavy-duty automatic transmissions, power steering units and hydraulic systems requiring Dexron III G and Allison C-4 fluids.

### FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors
- Especially effective in minimizing transmission “chatter.” Helps ensure smooth, quiet action at all speeds
- It ensures fast circulation during cold weather and excellent lubrication when hot

### OEM Approvals:

- ZF TE-ML 04D, 14A
- VOITH H55.6335.xx

### PERFORMANCE LEVELS: Meets or Exceeds:

- ALLISON TES-389
- ALLISON C4
- MAN 339 TYPE V1 /Z1/V2/Z2
- MB 236.1/236.10/236.5/236.6/236.9
- AISIN WARNER JWS 3309
- BMW 83 22 0 403 248
- BMW 83 22 2 163 514
- BMW 83 22 9 407 765 (LA 2634)
- BMW 83 22 9 407 807
- BMW 7045E (3 Series)
- BMW ETL-8072B (5 Series)
- BMW LT71141 (ZF 5 Speed)
- CHRYSLER ATF+3
- CHRYSLER ATF+4
- DAIHATSU ALUMIX ATF MULTI
- FORD M, FORD TASA
- FORD Mercon V
- FORD Mercon SP
- FORD Mercon LV
- FORD Mercon ATF Type F
- FORD XT-8-QMM5 [FRN5]
- GM Dexron II D
- GM Dexron II E
- GM Dexron III F
- GM Dexron III G
- GM Dexron III H
- HONDA ATF-Z1 (not for CVT)
- HONDA ATF DW-1
- HYUNDAI ATF SP-II
- HYUNDAI ATF SP-III
- INFINITI Matic D
- INFINITI Matic J
- INFINITI Matic K
- IDEMITSU K17-Jaguar X Type 2001-2005
- JATCO ATF 3100 PL085
- KIA ATF-SP-II
- KIA ATF-SP-III
- LEXUS ATF Type T
- LEXUS ATF Type T-II
- LEXUS ATF Type T-III
- LEXUS ATF Type T-IV
- LT 71141
- MAN 339 F
- MAN 339 V1
- MAN 339 V2
- MAN 339 Z1
- MAN 339 Z2
- MAZDA ATF M-III
- MAZDA ATF M-V
- MB 236.1
- MB 236.2
- MB 236.3
- MB 236.5
- MB 236.6
- MB 236.7
- MB 236.9
- MB 236.10
- MB 236.11
- MITSUBISHI DIAMOND SP-II
- MITSUBISHI DIAMOND SP-III
- MOPAR A668RC
- NISSAN Matic D
- NISSAN Matic J
- NISSAN Matic K
- PORSCHE JWS 3309
- SUBARU ATF-5
- SUBARU ATF-HP
- SUZUKI 3314
- SUZUKI 3317
- SUZUKI 2384K
- SUZUKI ATF OIL
- SUZUKI ATF OIL SPECIAL
- TOYOTA ATF Type T
- TOYOTA ATF Type T-II
- TOYOTA ATF Type T-III
- TOYOTA ATF Type T-IV
- VOLVO 1161621, 97341
- VOLKSWAGEN G 052 025-A2
- VOLKSWAGEN G 052 162-A1
- VOLKSWAGEN G 052 990-A1
- VOLKSWAGEN G 052 990-A2
- VOLKSWAGEN G 055 025-A1
- VOLKSWAGEN G 055 025-A2
- VOITH 55.6335.XX (G607)
- VOITH 55.6336.3x
- VOLVO 97340
- VOLVO 97341
- ZF TE-ML 03D
- ZF TE-ML 04D
- ZF TE-ML 09C
- ZF TE-ML 11B
- ZF TE-ML 14A
- ZF TE-ML 14B
- ZF TE-ML 16L
- ZF TE-ML 17C

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	ATF DEX III
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C, min	ASTM D7042	cSt	7.2
Viscosity Index	ASTM D2270	-	140
Density@15°C/ 60°F	ASTM D4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.revionoil.com](http://www.revionoil.com)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet [www.revionoil.com](http://www.revionoil.com)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

### ™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.