



Revion Duramax Diesel Engine Oil Mineral

PRODUCT DESCRIPTION:

Revion Duramax diesel engine oil is an advanced mineral diesel engine oil that maximizes engine performance in the latest US, European and Japanese heavy-duty diesel engines including severe applications such as high loads and multi-trailer operations.

APPLICATION:

Recommended for new advanced diesel powered engines in trucks, marine industries, heavy-duty construction equipment, mining equipment, farm vehicles, passenger cars, operating under severe conditions and subjected to wide variations in climatic conditions, in all types of on-road and off-road service. They are also recommended for gasoline engines in pick-up trucks, sport utility vehicles and mixed fleets.

FEATURES & BENEFITS:

- Fights oil thickening due to its unique additive system, it delivers superior viscosity stability, resulting in better fuel efficiency.
- Prevents piston deposits by minimising harmful deposits, resulting in lower oil consumption.
- Fights contaminants, resulting in longer oil drain intervals.
- Prevents wear and corrosion by providing a robust oil film, enhancing the life of critical engine components
- Formulated with lower levels of Sulphated Ash.
- Phosphorous and Sulphur than conventional oils to maintain the efficiency of exhaust after treatment systems eg. DPF or DPD
- Fights soot abrasive wear, improving engine power all the way through the oil drain

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CJ-4/SN
- ACEA E9/E11
- DTRF 15B1101
- Caterpillar ECF-3
- MAN M3477
- VOLVO VDS-4
- Renault RLD3
- DDC 93K218
- Mack EO-O PP
- Cummins CES 20081
- DEUTZ DQC III-18 LA
- FORD WSS-M2C171-F1

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	REVION DURAMAX DIESEL ENGINE OIL		
			15W-40	20W-50	50
Grade					
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	15.2	19.5	
Viscosity Index (min)	D2270	-	135	120	
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	
Flash Point (min)	D92	°C	220	220	
Pour Point (max)	D97	°C	-33	-24	
TBN	D2896	mg KOH/g	10	10	
CCS	D5293	m.Pa.S	<7000 (-20°C)	<9500 (-15°C)	

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.revionoil.com

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet www.revionoil.com

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 600C, exposed to hot sun or freezing conditions.

™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.