



## Revion Brake Fluid

### PRODUCT DESCRIPTION:

Dot-4 has been specially designed for use in heavy-duty brake systems of vehicles that require a DOT 4 synthetic brake fluid. The product is particularly recommended for brake systems with ABS. STOP DOT-4 Brake Fluid can be mixed with all synthetic brake fluids of the same grade.

### APPLICATION:

Dot-4 is designed to excel within the extreme demands made on a race vehicle or by high performance drivers and exceeds all DOT4 standards. It is compatible with and will mix well with most DOT3, DOT4 or DOT 5.1 fluids.

### FEATURES & BENEFITS:

- High dry boiling point
- High wet boiling point
- High lubricating power
- Exceptional low viscosity at low temperature
- Miscibility with all brake fluids of the same specification

### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- ISO 4925 Class 6
- FMVSS 116 DOT 4
- SAE J 1704
- MB 276.40

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DOT 4
Kinematic Viscosity @100C	D445	cSt	2.1
Kinematic Viscosity @-40C	D445	cSt	TBR
Boiling Point (Reflux)	D1120	°C	230
Wet Boiling Point	D1120	°C	180
Density@ 15°C	D4052	g/ml	TBR

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.revionoil.com](http://www.revionoil.com)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet [www.revionoil.com](http://www.revionoil.com)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 600C, exposed to hot sun or freezing conditions.

### ™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.