



Revion Active Engine Oil Mineral

PRODUCT DESCRIPTION:

Revion Active Engine oil is premium quality mineral oil for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is particularly suited to turbo-charged engines and perfectly adapted to vehicles equipped with catalysts and using unleaded fuel.

APPLICATION:

Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	15W-40	20W-50	20W-60	25W-60	20W-40	25W-50
API	SL/CF	SL/CF	SL/CF	SL/CF		
ACEA	A3/B3/B4	A3/B3/B4	A3/B3/B4	A3/B3/B4		
RENAULT	RN0700/ RN0710	RN 0700/0710	-	-		
VW	501.01 / 505	501.01 / 505	501.01 / 505	-		

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	REVION ACTIVE ENGINE OIL					
			15W-40	20W-50	20W-60	25W-60	20W-40	25W-50
SAE Grades								
Kinematic Viscosity @ 104°F /40°C	D445	cSt	TBR	TBR	TBR	TBR		
Kinematic Viscosity @ 212°F /100°C	D445	cSt	15	20.2	24.2	24.0		
Viscosity Index (min)	D2270	-	142	131	145	124		
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR		
Flash Point (min)	D92	°C	220	220	220	220		
Pour Point (max)	D97	°C	-33	-24	-24	-21		
TBN	D2896	mg KOH/g	8	8	8	8		
CCS	D5293	m.Pa.S	<7000 (-35°C)	<9500 (-15°C)	<9500 (-15°C)	<13,000 (-10°C)		

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.revionoil.com

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet www.revionoil.com

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 600C, exposed to hot sun or freezing conditions.

™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.