



## Revion Apex Engine oil Semi Synthetic

### PRODUCT DESCRIPTION:

Revion Apex engine oils is an advanced engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. It meets the requirements of the latest industry standards for "Full SAPS" passenger car lubricants and outperforms conventional oils. These oils are designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and excellent low temperature performance over the life of the oil.

### APPLICATION:

Recommended for gasoline fueled automobiles and light-duty trucks requiring an API Service Category SN/CF.

### FEATURES & BENEFITS:

- Outstanding wear protection under a wide variety of operating conditions
- Special cleaning additive to help prevent the formation of sludge and harmful deposits
- Optimal engine operating temperature, owing to thermal control formula
- Limits formation of deposits on the most loaded engine parts
- Provides safe operation of catalytic exhaust converters
- Resistant to extreme thermal load, due to high quality of base oil
- Enables fast and easy start in extreme temperature conditions
- Extra cleaning performance

### PERFORMANCE LEVELS /MEETS OR EXCEEDS:

This product is recommended for use in applications requiring:

- API SN/CF
- ACEA A3/B3/B4
- MB 229.3/226.5
- Renault RN0700/RN0710

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	REVION APEX ENGINE OIL	
			10W30	10W40
<b>Grade</b>			<b>10W30</b>	<b>10W40</b>
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.5	14.9
Viscosity Index (min)	D2270	-	145	145
Density@15°C/ 60°F	D4052	g/cm³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	Mg KOH/g	10	10
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

### P.S:

This product is available in both synthetic and semi synthetic specifications.

**DISCLAIMER:** The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Revion reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.revionoil.com](http://www.revionoil.com)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales Office or via the internet [www.revionoil.com](http://www.revionoil.com)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 600C, exposed to hot sun or freezing conditions.

### ™ Trademark of Revion, Registered in Various Countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Revion and its affiliates assume legal responsibility.